

Key Features

- Lifelike True Beauty: International color standard Pantone validated and 100% sRGB wide color gamut
- Precise Color: ColorPro Verified with prefactory calibration for overwhelmed Delta E <
 2 color accuracy
- Multimedia Devices: Support USB-C with 60W high-speed charging, plus HDMI 2.0, DisplayPort 1.4, USB3.2
- Unlimited Flexibility: Auto Pivot & Ergonomic Stand with tilt, swivel, pivot, and height adjustments
- The Visible Difference: 4K UHD(3840* 2160) resolution IPS panel with 27" frameless design



Product **Description**

Designed with creative professionals in mind, the ViewSonic VP2756-4k delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us www.

www.viewsonic.com

DISPLAY		CONTROLS	
Display Size (in.):	27	Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
Viewable Area (in.):	27		Input Select, Audio Adjust, ViewMode
Panel Type:	IPS Technology	On Screen Display:	Color Adjust, Manual Image Adjust, Setup Menu
Resolution:	3840 x 2160	OPERATING CONDITIONS	
Resolution Type:	UHD (Ultra HD)	Temperature:	32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	1,000:1 (typ)	Humidity (non-condensing):	20% to 90%
Dynamic Contrast Ratio:	20M:1	WALL MOUNT	
Light Source:	LED	VESA Compatible:	100 x 100 mm
Brightness:	350 cd/m² (typ)	INPUT SIGNAL	
Colors:	1.07B	Frequency Horizontal:	15 ~ 136KHz
Color Space Support:	10 bit (8 bit + A-FRC)	Frequency Vertical:	24 ~ 75Hz
Aspect Ratio:	16:9	VIDEO INPUT	
Response Time (Typical GTG):	5ms	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2), Micro-Packet - Type C
Response Time (GTG w/OD):	5ms		
Viewing Angles:	178º horizontal, 178º vertical	ERGONOMICS	
Backlight Life (Hours):	30000 Hrs (Min)	Height Adjust (mm):	130
Curvature:	Flat	Swivel:	120°
Refresh Rate (Hz):	60	Tilt (Forward/Back):	-5° / 21°
Blue Light Filter:	Yes	Pivot (Right/Left):	90° / 90°
Flicker-Free:	Yes	WEIGHT (IMPERIAL)	
Color Gamut:	Adobe RGB: 81% size / 78%	Net (Ibs):	16.6
	coverage (Typ) DCI-P3: 80% size / 80% coverage	Net Without Stand (lbs):	11.2
	(Typ) EBU: 108% size / 98% coverage (Typ)	Gross (lbs):	22.5
	REC709: 109% size / 100% coverage (Typ) SMPTE-C: 118% size / 100% coverage (Typ) NTSC: 77% size (Typ) sRGB: 109% size / 100% coverage	WEIGHT (METRIC)	
		Net (kg):	7.5
		Net Without Stand (kg):	5.1
	(Тур)	Gross (kg):	10.2
Pixel Size:	0.155 mm (H) x 0.155 mm (V)	DIMENSIONS (IMPERIAL) (W	/XHXD)
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Packaging (in.):	29.1 x 18.3 x 8.9
OMPATIBILITY		Physical (in.):	24.1 x 16.15~21.27 x 8.5
PC Resolution (max):	3840x2160	Physical Without Stand (in.):	24.1 x 14.3 x 2.1
Mac® Resolution (max):	3840x2160	DIMENSIONS (METRIC) (WX	HXD)
PC Operating System:	Windows 10/11 certified; macOS tested	Packaging (mm):	740 x 465 x 225
Mac@ Baselutian (min)	3840x2160	Physical (mm):	613 x 410.31~540.31 x 215
Mac® Resolution (min): CONNECTOR	304072100	Physical Without Stand (mm):	613 x 363 x 53
USB 3.2 Type A Down Stream:	2	GENERAL	
USB 3.2 Type B Up Stream:	1		cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico
USB 3.2 Type C Up Stream;		Regulations:	Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC,
DisplayPort Alt mode :	1		UkrSEPRO, UKCA, BIS, CCC, China RoHS, China Energy Label, CECP
HDMI 2.0 (with HDCP 2.2):	2		VP2756-4K x1, 3-pin Plug (IEC C13 /
DisplayPort:	1		CEE22) x1, HDMI Cable (v2.0; Male-
Power in:	3-pin Socket (IEC C14 / CEE22)	PACKAGE CONTENTS:	Male) x1, USB Type-C Cable (Male- Male) x1, USB A/B Cable (v3.2; Male- Male) x1, Oxiale Cable (v3.2; Male-
UDIO			Male) x1, Quick Start Guide x1
Internal Speakers:	2Watts x2	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
OWER		Warranty:	*Warranty offered may differ from
Eco Mode (Conserve):	19.3W		market to market
Eco Mode (optimized):	21.5W	Power Management:	Energy Star standards, EPEAT
Consumption (typical):	24W		
Consumption (max):	28W		
Voltage:	AC 100-240V		
Stand-by:	0.3W		
Power Supply:	Internal Power Supply		
DDITIONAL HARDWARE			
Kensington Lock Slot:	1		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.